SAFETY DATA SHEET Per OSHA HCS

PAGE 1

Date SDS Printed & Reviewed: 09/30/16 Last Formula Revision Date: 09/09/16

(SPE)

SECTION 1: IDENTIFICATION

PRODUCT IDENTIFIER:

WTCT

WETSTEPS

CANDY TEAL

OTHER MEANS OF IDENTIFICATION (FOR CHEMTREC): FORMULA # 33A452N0.5

RECOMMENDED USE OF THE CHEMICAL: LIQUID COATING

SUPPLIER DETAILS: MANUFACTURED BY:

MANUFACTURED FOR: (C3298)

Custom-Pak Products Inc.

N118 W 18981 Bunsen Drive

Germantown, WI 53022

(262) 251-6180

CERAMIFIX LLC

641 BUCKINGHAM DRIVE

CAMDENTON, MO 65020

573-873-6280

EMERGENCY 24-HOUR TELEPHONE NUMBERS:

Call CHEMTREC: within USA dial 1-800-424-9300 or outside USA dial +1-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OF MIXTURE:

Flammable Liquids, Category 3

Specific Target Organ Toxicity - Single Exposure, Category 3

HAZARD PICTOGRAMS:

GHS02 Flame, GHS07 Exclamation Mark

SIGNAL WORD: WARNING

HAZARD STATEMENTS:

H226 Flammable liquid and vapor.

H336 May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS:

GENERAL & PREVENTION:

P102 Keep out of reach of children.

P210 Keep away from heat/sparks/open flames/other ignition sources. No smoking.

P233 Keep container tightly closed when not in use.

P261-1 Avoid breathing vapor.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection.

RESPONSE:

P304+P340 IF INHALED: Remove victim to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P370+P378 In case of fire: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agent

P403+P233 Store in a well-ventilated place. Keep container tightly closed when not in use.

P403+P235 Store in a well-ventilated place. Keep cool.

DISPOSAL:

P501 Dispose of contents/container in accordance with local/regional/national regulations.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT IDENTIFIER:

WTCT WETSTEPS CANDY TEAL

#	COMPONENT	CAS#	% by WT.
1	N-BUTYL ACETATE	123-86-4	40-51
2	ETHYL ESTER	763-69-9	8-10
3	PM ACETATE	108-65-6	1-3
4	METHYL ETHYL KETOXIME	96-29-7	0.1-1
5	ALIPHATIC PETROLEUM NAPHTHA	64742-48-9	0.1-1
6	SOLVENT NAPHTHA	64742-95-6	0.1-1
7	(BIN 14) ALTPHATIC HYDROCARBON	8052-41-3	0.1-1

SECTION 4 - FIRST AID MEASURES

Inhalation: If inhaled: Move victim to fresh air and keep comfortable for breathing.

Skin Contact: If on skin: Wash with plenty of soap and water. Call a poison center/doctor if you feel unwell.

Remove contaminated clothing and wash before reuse.

Eye Contact: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

See Section 11: Toxicological Information and effects.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT REQUIRED:

Treat symptomatically.

SECTION 5 - FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: CO2 (Carbon Dioxide), dry chemical, or water fog.

Unsuitable Extinguishing Media: Water spray may be unsuitable. However if water is used fog nozzles are preferable.

Water may be used to cool closed containers to prevent pressure build-up.

Specific Hazards Arising From the Chemical: Closed containers exposed to heat from fire may build pressure and explode. Products of combustion may include but are not limited to: oxides of carbon.

Special Protective Equipment and Precautions for Fire-Fighters: Full protective equipment including self-contained breathing apparatus should be used.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Prevent contamination of soil/ground, waterways, drains, and sewers.

Methods of Containment: Absorb spilled liquid in suitable material.

Methods for Clean-Up: Use spark-proof tools to sweep or scrape up, containerize, and dispose of properly.

Other Information: Ensure adequate ventilation.

SECTION 7 - HANDLING AND STORAGE

Precautions for Safe Handling:

Vapors may ignite explosively. Prevent buildup of vapors. Keep from sparks, heat, flame or other heat sources. Do not smoke. Turn off pilot lights, heaters, electric motors and other sources of ignition during use and

CONTINUED -->

PRODUCT IDENTIFIER:

WTCT WETSTEPS CANDY TEAL

----until all vapors are gone. Do not puncture or incinerate/burn container. Keep container tightly closed while not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in dry, well-ventilated area and in accordance with federal, state, and local regulations. Do not expose to heat or store at temperatures above 50 degrees C / 122 degrees F. If storing in cold temperatures, allow product to warm to room temperature before use. Keep container tightly closed and away from heat and sunlight when not in use.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

#	COMPONENT	ACGIH TLV-STEL	ACGIH TLV-TWA	OSHA PEL-TWA
1	N-BUTYL ACETATE	200 ppm	150 ppm	150 ppm
2	ETHYL ESTER	100 ppm	50 ppm	N/E
3	PM ACETATE	N/E	N/E	N/E
4	METHYL ETHYL KETOXIME	N/E	N/E	N/E
5	ALIPHATIC PETROLEUM NAPHTHA	N/E	100 ppm	500 ppm
	SOLVENT NAPHTHA	N/E	100 ppm	100 ppm
	(BIN 14) ALIPHATIC HYDROCARBON	N/E	N/E	N/E

APPROPRIATE ENGINEERING CONTROLS: Provide adequate ventilation to keep air contamination below OSHA permissible exposure limits and ACGIH TLV exposure levels. Ground containers during fluid transfers.

EYE/FACE PROTECTION: Wear safety glasses with side shields. Have eye wash facilities immediately available.

SKIN PROTECTION: Wear chemical resistant gloves if contact is likely.

RESPIRATORY PROTECTION: Use NIOSH-approved air-purifying respirator with organic cartridge or canister if exposure cannot be controlled within applicable limits with ventilation.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:

Liquid

COLOR:

See product identification

ODOR:

Solvent Odor

ODOR THRESHOLD:

No Data Available No Data Available

FREEZING POINT:

Not established (mixture)

BOILING POINT:

75 - 186 degrees C (167 - 367 degrees F)

FLASH POINT:

greater than 23 degrees C (greater than 73 degrees F), c.c.

EVAPORATION RATE:

VAPOR PRESSURE:

Slower than ether

UPPER FLAMMABILITY LIMIT: Not established (mixture)

LOWER FLAMMABILITY LIMIT: Not established (mixture)

Not established (mixture)

SPECIFIC GRAVITY: SOLUBILITY (WATER): 0.970

VOC PERCENT BY WEIGHT:

Negligible

61.87

HAPS PERCENT BY WEIGHT:

SECTION 10: STABILITY AND REACTIVITY

PRODUCT IDENTIFIER:

WTCT WETSTEPS CANDY TEAL

CHEMICAL STABILITY: Stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS: Will not occur.

CONDITIONS TO AVOID: Keep away from heat, sparks, and flames.

INCOMPATIBLE MATERIALS: Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: by fire - Carbon Dioxide and Carbon Monoxide

SECTION 11: TOXICOLOGICAL INFORMATION

LIKELY ROUTES OF ENTRY: Skin contact, Inhalation, Eye contact, Ingestion

SIGNS AND SYMPTOMS OF EXPOSURE:

Skin Contact: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

Intentional concentration and inhalation may be harmful or fatal. Inhalation:

Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the Eye Contact:

cornea, and impaired vision.

Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. Ingestion:

Intentional concentration and ingestion of large amounts may be harmful or fatal.

TARGET ORGANS POTENTIALLY AFFECTED BY EXPOSURE:

Central nervous system, kidneys, lungs, liver, eyes, skin, brain, respiratory tract, urinary tract, reproductive system, cardiovascular system

TOXICOLOGICAL DATA:

#	COMPONENT	LD50 ORAL	LD50 DERMAL	LC50 INHALATION
1.	N-BUTYL ACETATE	>10,760 mg/kg (rat)	>14,112 mg/kg rabbit	
2.	ETHYL ESTER	N/E	N/E	N/E
3.	PM ACETATE	>5000 mg/kg (rat)	>5000 mg/kg (rabbit)	>10.8 mg/l (rat)
4.	METHYL ETHYL KETOXIME	N/E	N/E	N/E
5.	ALIPHATIC PETROLEUM NAPHTHA	N/E	N/E	N/E
6.	SOLVENT NAPHTHA	N/E	N/E	N/E
7.	(BIN 14) ALIPHATIC HYDROCARBON	N/E	N/E	N/E

SECTION 12: ECOLOGICAL INFORMATION

No Data Available

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of container and its contents in accordance with federal, state, and local regulations. Do not puncture, incinerate, or place container in trash compactor.

SECTION 14: TRANSPORTATION INFORMATION

GROUND (D.O.T./49 CFR)

UN I.D. Number: UN1263 Proper Shipping Name:

PAINT

Transport Hazard Class: 3 Packing Group:

III

Hazard Label:

Limited Quantity (LTD QTY) label -- see 49 CFR 172.315

Shipping papers format:

UN1263, PAINT, 3, III, LTD QTY

CONTINUED -->

SAFETY DATA SHEET Per OSHA HCS

PRODUCT IDENTIFIER:

WTCT WETSTEPS CANDY TEAL -----

SPECIAL NOTE:

If containers have less than 30ml (1 fl.oz.) flammable liquid, they may be

exempt from 49 CFR - see 49 CFR 173.4 Small Quantity Exceptions Note that outer package needs statement "This package conforms to

49 CFR 173.4 for domestic highway or rail transport only."

AIR (IATA)

UN I.D. Number:

UN1263 Proper Shipping Name:

PAINT

Transport Hazard Class: 3 Packing Group:

III

Hazard Label:

LTD QTY label with "Y", and Flammable Liquid label

Packing Instruction:

Y344 (Note 10L maximum per package!)

Shipping papers format:

UN1263, PAINT, 3, III

SPECIAL NOTE:

If containers have less than 30ml (1 fl. oz.), they may qualify to be shipped

as Excepted Quantity - see IATA 2.6 for details.

WATER (IMDG)

UN I.D. Number:

UN1263 Proper Shipping Name:

PAINT

Transport Hazard Class:

3 Packing Instructions:

P001, LP01

Packing Group:

III Hazard Label:

LTD QTY label, see IMDG 3.4.5.1

Shipping papers format:

F-E, S-E Stowage and Segregation: Category A

UN1263, PAINT, 3, III, (23 C c.c.), LTD QTY

SPECIAL NOTE:

If containers have less than 30ml (1 fl. oz.), they may qualify to be shipped

as an Excepted Quantity, see IMDG 3.5.1 for details.

No component of this product is a listed Marine Pollutant (49 CFR 172,101,Appendix B).

SECTION 15: REGULATORY INFORMATION

International Chemical Inventory

All components of this product are listed on or exempt from the following inventories:

TSCA (United States), CEPA/DSL (Canada), AICS (Australia), IECSC (China)

SECTION 16: OTHER INFORMATION

REVISION DATE: 09/09/16

HMIS & NFPA Hazard Scale:

0=minimal, 1=slight, 2=moderate, 3=serious, 4=severe

HMIS(American Coatings Association's Hazardous Material Identification System):

Flammability = 3 Physical Hazard = 1 Health = 2

NFPA 704(National Fire Protection Association's Hazard Identification Ratings System):

Flammability = 3 Instablity = 1 Health = 2

This SDS is based on information believed to be reliable and accurate. Because of changing reporting requirements and other variables it is impossible to guarantee with complete accuracy all the information contained in this document. It is the responsibility of the user to determine proper personal protection based on actual condition of use and to comply with all federal, state, and local laws and regulations.